

smartmi

Color Image of product:



smartmi

Technical Information

Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only (select one)	
Nominal heat output	Pnom	2.2	KW	manual heat charge control, with integrated thermostat	Not applicable
Minimum heat output (indicative)	Pmin	0.9	KW	manual heat charge control with room and/or outdoor temperature feedback	Not applicable
Maximum continuous heat output	Pmax,c	2.2	KW	electronic heat charge control with room and/or outdoor temperature feedback	Not applicable
Auxiliary electricity consumption				fan assisted heat output	
				Not applicable	
At nominal heat output	elmax	2.200	KW	Type of heat output/room temperature control (select one)	
At minimum heat output	elmin	0.900	KW	single stage heat output and no room temperature control	[no]
In standby mode	eISB	0.000	KW	Two or more manual stages, no room temperature control	[no]
				with mechanic thermostat room temperature control	[no]
				with electronic room temperature control	[yes]
				electronic room temperature control plus day timer	[no]
				electronic room temperature control plus week timer	[no]
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	[no]
				room temperature control, with open window detection	[no]
				with distance control option	[yes]
				with adaptive start control	[no]
				with working time limitation	[no]
				with black bulb sensor	[no]
Contact details		Beijing Smartmi Electronic Technology Co., Ltd. Room 6111, 1st Floor, Building 6, No.18 Xueqing Road, Haidian District, Beijing, China			